



Steer and trailer tire for a wide range of trucks and buses, including Light Duty all position applications.

### Features

Five straight rib pattern design

Deep tread depth

Multiple sipes in five ribs

### Benefits

- ▶ Superior control and handling
- ▶ Long original tread life
- ▶ Optimal traction and braking

### SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)						Inch
10R22.5	100EV477G	16	H	144/142 M	7.50	6.75	6,175@130	5,840@130	10	18.7	40.1	17.6	518	108
255/70R22.5	100EV591G	16	H	140/137 M	7.50	8.25	5,510@120	5,070@120	10.0	17.1	36.6	17	568	93
275/70R22.5	100EV627G	16	H	148/145 M	8.25	9.00	6,945@130	6,395@130	10.9	17.5	37.7	19	551	111
11R22.5	100EV794G	14	G	144/142 M	8.25	7.50	6,175@105	5,840@105	11.0	19.3	41.5	21	501	125
11R22.5	100EV611G	16	H	148/145 M	8.25	7.50	6,940@120	6,395@120	11.0	19.3	41.5	21	501	125
295/75R22.5	100EV693G	14	G	144/141 M	9.00	8.25	6,175@110	5,675@110	11.7	18.7	39.9	20	521	121
11R24.5	100EV679G	14	G	146/143 M	8.25	7.50	6,610@105	6,005@105	11.0	20.3	43.5	19	478	131
11R24.5	100EV682G	16	H	149/146 M	8.25	7.50	7,160@120	6,610@120	11.0	20.3	43.5	19	478	133
285/75R24.5	100EV761G	14	G	144/141 M	8.25	N/A	6,175@110	5,675@110	11.1	19.4	41.3	19	503	120

### LIGHT DUTY SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)						Inch
225/70R19.5	100EV650G	14	G	128/126 J	6.75	6.00	3,970@110	3,750@110	8.9	14.9	31.9	16	651	70
245/70R19.5	100EV662G	16	H	136/134 M	7.50	6.75	4,940@120	4,675@120	9.8	15.3	33.0	17	630	77

PR Ply Rating    LR Load Range    SR Speed Rating    SLR Static Loaded Radius

Giti Tire Manufactures SmartWay Verified Technologies. Learn more at [epa.gov/smartway](http://epa.gov/smartway).